

HYDROTAP G5 CLASSIC PLUS WITH ARC MIXER BOILING CHILLED 160/175







BOILING

CHILLED

HOT & COLD

FILTERED

UNFILTERED

Order Code H55604Z00UK

Discover the Zip Water HydroTap Classic Plus with Arc mixer, providing instant filtered boiling and chilled plus hot and cold water for your office or workplace.

Manufacturing Code	H55604Z00UK
Capacity	Commercial
Number of people	60
Boiling Cups per hour	160
Chilled Cups per hour	175
Chilled Litres per hour	175



Tap HydroTap Classic Plus + Arc Mixer bright chrome Water Pressure Min 1.7 bar - Max 5 bar Water Connection 1/2" BSP Water Supply Requirements Water Valves Integrated dual check valve Power Rating 2.1kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA Warranty Appliance warranty 24 months plus additional 36 months boiling tank warranty		
Water Connection1/2" BSPWater Supply RequirementsCold & HotWater ValvesIntegrated dual check valvePower Rating2.1kW 230v 50/60 HzPower Supply1 x 13 ampDimensionsW500mm x D520mm x H373mmProduct ApprovalsCE, UKCA	Тар	HydroTap Classic Plus + Arc Mixer bright chrome
Water Supply Requirements Water Valves Integrated dual check valve Power Rating 2.1kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Water Pressure	Min 1.7 bar - Max 5 bar
Requirements Water Valves Integrated dual check valve Power Rating 2.1kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Water Connection	1/2" BSP
Power Rating 2.1kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA		Cold & Hot
Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Water Valves	Integrated dual check valve
Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Power Rating	2.1kW 230v 50/60 Hz
Product Approvals CE, UKCA	Power Supply	1 x 13 amp
	Dimensions	W500mm x D520mm x H373mm
Warranty Appliance warranty 24 months plus additional 36 months boiling tank warranty	Product Approvals	CE, UKCA
	Warranty	Appliance warranty 24 months plus additional 36 months boiling tank warranty

Installation Requirements

^{&#}x27;1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipindustries.co.uk'