

## HYDROTAP G5 CLASSIC PLUS BOILING CHILLED 240/175





**BOILING** 

**CHILLED** 

**FILTERED** 

## Order Code H55705Z01UK

The Zip Water HydroTap Classic Plus in bright chrome provides instant filtered boiling and chilled drinking water for your office or workplace.

Manufacturing Code	H55705Z01UK
Capacity	Commercial
Number of people	100
Boiling Cups per hour	240
Chilled Cups per hour	175
Chilled Litres per hour	175



TapHydroTap Classic Plus brushed chromeWater PressureMin 1.7 bar - Max 5 barWater Connection1/2" BSPWater Supply RequirementsColdWater ValvesIntegrated dual check valvePower Rating2.1kW 230v 50/60 HzBooster Power Rating2.2kW at 230VPower Supply2 x 13 ampDimensionsW500mm x D520mm x H373mmProduct ApprovalsCE, UKCAWarrantyAppliance warranty 24 months plus additional 36 months boiling tank warranty		
Water Connection1/2" BSPWater Supply RequirementsColdWater ValvesIntegrated dual check valvePower Rating2.1kW 230v 50/60 HzBooster Power Rating2.2kW at 230VPower Supply2 x 13 ampDimensionsW500mm x D520mm x H373mmProduct ApprovalsCE, UKCA	Тар	HydroTap Classic Plus brushed chrome
Water Supply Requirements  Water Valves Integrated dual check valve  Power Rating 2.1kW 230v 50/60 Hz  Booster Power Rating 2.2kW at 230V  Power Supply 2 x 13 amp  Dimensions W500mm x D520mm x H373mm  Product Approvals CE, UKCA	Water Pressure	Min 1.7 bar - Max 5 bar
RequirementsWater ValvesIntegrated dual check valvePower Rating2.1kW 230v 50/60 HzBooster Power Rating2.2kW at 230VPower Supply2 x 13 ampDimensionsW500mm x D520mm x H373mmProduct ApprovalsCE, UKCA	Water Connection	1/2" BSP
Power Rating         2.1kW 230v 50/60 Hz           Booster Power Rating         2.2kW at 230V           Power Supply         2 x 13 amp           Dimensions         W500mm x D520mm x H373mm           Product Approvals         CE, UKCA	* * *	Cold
Booster Power Rating         2.2kW at 230V           Power Supply         2 x 13 amp           Dimensions         W500mm x D520mm x H373mm           Product Approvals         CE, UKCA	Water Valves	Integrated dual check valve
Power Supply         2 x 13 amp           Dimensions         W500mm x D520mm x H373mm           Product Approvals         CE, UKCA	Power Rating	2.1kW 230v 50/60 Hz
Dimensions     W500mm x D520mm x H373mm       Product Approvals     CE, UKCA	Booster Power Rating	2.2kW at 230V
Product Approvals CE, UKCA	Power Supply	2 x 13 amp
···	Dimensions	W500mm x D520mm x H373mm
Warranty Appliance warranty 24 months plus additional 36 months boiling tank warranty	Product Approvals	CE, UKCA
	Warranty	Appliance warranty 24 months plus additional 36 months boiling tank warranty

## **Installation Requirements**

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipindustries.co.uk'