

HYDROTAP G5 CLASSIC PLUS BOILING CHILLED SPARKLING 160/175







BOILING

CHILLED

SPARKLING

FILTERED

Order Code H55762Z00UK

Get instant filtered boiling, chilled and sparkling tap water for your office or workplace from the Zip Water HydroTap Classic Plus in bright chrome.

Manufacturing Code	H55762Z00UK
Capacity	Commercial
Number of people	60
Boiling Cups per hour	160
Chilled Cups per hour	175
Chilled Litres per hour	175
Combined Chilled and Sparkling Cups per hour	175
Combined Chilled and Sparkling Litres per hour	175



TapHydroTap Classic Plus bright chromeWater PressureMin 2.5 bar - Max 5 barWater Connection1/2" BSPWater Supply RequirementsColdWater ValvesIntegrated dual check valvePower Rating2.15kW 230v 50/60 HzPower Supply1 x 13 ampDimensionsW500mm x D520mm x H373mmProduct ApprovalsCE, UKCAWarrantyAppliance warranty 24 months plus additional 36 months boiling tank warranty		
Water Connection 1/2" BSP Water Supply Cold Requirements Water Valves Integrated dual check valve Power Rating 2.15kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Тар	HydroTap Classic Plus bright chrome
Water Supply Requirements Water Valves Integrated dual check valve Power Rating 2.15kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Water Pressure	Min 2.5 bar - Max 5 bar
Requirements Water Valves Integrated dual check valve Power Rating 2.15kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Water Connection	1/2" BSP
Power Rating 2.15kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA		Cold
Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Water Valves	Integrated dual check valve
Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Power Rating	2.15kW 230v 50/60 Hz
Product Approvals CE, UKCA	Power Supply	1 x 13 amp
	Dimensions	W500mm x D520mm x H373mm
Warranty Appliance warranty 24 months plus additional 36 months boiling tank warranty	Product Approvals	CE, UKCA
	Warranty	Appliance warranty 24 months plus additional 36 months boiling tank warranty

Installation Requirements

1. Installation and connection of your Zip HydroChill must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections within 1 metre of the product.3. Discrete cabinetry cut-outs are required for ventilation.4. Installation for HydroChill 50 on most bench tops is straightforward, however some stone bench tops may require a specialised cutting service.5. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.co.uk