

## HYDROTAP G5 CLASSIC PLUS BOILING CHILLED SPARKLING 160/175







BOILING

**CHILLED** 

**SPARKLING** 

**FILTERED** 

## Order Code H55762Z03UK

Get instant filtered boiling, chilled and sparkling tap water for your office or workplace from the Zip Water HydroTap Classic Plus in bright chrome.

H55762Z03UK
Commercial
60
160
175
175
175
175



Tap HydroTap Classic Plus matt black  Water Pressure Min 2.5 bar - Max 5 bar  Water Connection 1/2" BSP  Water Supply Requirements  Water Valves Integrated dual check valve  Power Rating 2.15kW 230v 50/60 Hz  Power Supply 1 x 13 amp  Dimensions W500mm x D520mm x H373mm  Product Approvals CE, UKCA  Warranty Appliance warranty 24 months plus additional 36 months boiling tank warranty		
Water Connection 1/2" BSP  Water Supply Cold Requirements  Water Valves Integrated dual check valve  Power Rating 2.15kW 230v 50/60 Hz  Power Supply 1 x 13 amp  Dimensions W500mm x D520mm x H373mm  Product Approvals CE, UKCA	Тар	HydroTap Classic Plus matt black
Water Supply Requirements  Water Valves Integrated dual check valve  Power Rating 2.15kW 230v 50/60 Hz  Power Supply 1 x 13 amp  Dimensions W500mm x D520mm x H373mm  Product Approvals  CE, UKCA	Water Pressure	Min 2.5 bar - Max 5 bar
Requirements  Water Valves Integrated dual check valve  Power Rating 2.15kW 230v 50/60 Hz  Power Supply 1 x 13 amp  Dimensions W500mm x D520mm x H373mm  Product Approvals CE, UKCA	Water Connection	1/2" BSP
Power Rating         2.15kW 230v 50/60 Hz           Power Supply         1 x 13 amp           Dimensions         W500mm x D520mm x H373mm           Product Approvals         CE, UKCA	• • •	Cold
Power Supply         1 x 13 amp           Dimensions         W500mm x D520mm x H373mm           Product Approvals         CE, UKCA	Water Valves	Integrated dual check valve
Dimensions     W500mm x D520mm x H373mm       Product Approvals     CE, UKCA	Power Rating	2.15kW 230v 50/60 Hz
Product Approvals CE, UKCA	Power Supply	1 x 13 amp
	Dimensions	W500mm x D520mm x H373mm
Warranty Appliance warranty 24 months plus additional 36 months boiling tank warranty	Product Approvals	CE, UKCA
	Warranty	Appliance warranty 24 months plus additional 36 months boiling tank warranty

## **Installation Requirements**

1. Installation and connection of your Zip HydroChill must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections within 1 metre of the product.3. Discrete cabinetry cut-outs are required for ventilation.4. Installation for HydroChill 50 on most bench tops is straightforward, however some stone bench tops may require a specialised cutting service.5. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.co.uk