



HYDROTAP G5 CLASSIC PLUS BOILING CHILLED SPARKLING 140/75



BOILING



CHILLED



SPARKLING

FILTERED

Order Code H55764Z01UK

Discover the Zip Water HydroTap Classic Plus in bright chrome, providing instant filtered boiling, chilled and sparkling tap water for your office or workplace.

Manufacturing Code H55764Z01UK

Capacity Commercial

Number of people 40

Boiling Cups per hour 140

Chilled Cups per hour 75

Chilled Litres per hour 75

Combined Chilled and Sparkling Cups per hour 75

Combined Chilled and Sparkling Litres per hour 75



Tap HydroTap Classic Plus brushed chrome

Water Pressure Min 2.5 bar - Max 5 bar

Water Connection 1/2" BSP

Cold

Water Supply Requirements

Water Valves	Integrated dual check valve
Power Rating	1.96kW 230v 50/60 Hz
Booster Power Rating	2.2kW at 230V
Power Supply	2 x 13 amp
Dimensions	W339mm x D483mm x H333mm
Product Approvals	CE, UKCA
Warranty	Appliance warranty 24 months plus additional 36 months boiling tank warranty

Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipindustries.co.uk'