

HYDROTAP G5 CLASSIC PLUS WITH ARC MIXER BOILING CHILLED SPARKLING 160/175









BOILING

CHILLED

SPARKLING

HOT & COLD

FILTERED

UNFILTERED

Order Code H55875Z00UK

Discover the Zip Water HydroTap Classic Plus with Arc mixer, providing instant filtered boiling, chilled and sparkling water plus hot and cold water for your office or workplace.

| Manufacturing Code | H55875Z00UK |
|---|-------------|
| Capacity | Commercial |
| Number of people | 60 |
| Boiling Cups per hour | 160 |
| Chilled Cups per hour | 175 |
| Chilled Litres per hour | 175 |
| Combined Chilled and Sparkling Cups per hour | 175 |
| Combined Chilled and Sparkling Litres per hour | 175 |
| | |



| Тар | HydroTap Classic Plus + Arc Mixer bright chrome |
|------------------|---|
| Water Pressure | Min 2.5 bar - Max 5 bar |
| Water Connection | 1/2" BSP |
| | Cold & Hot |

| Water Supply Requirements | |
|------------------------------|--|
| Water Valves | Integrated dual check valve |
| Power Rating | 2.15kW 230v 50/60 Hz |
| Power Supply | 1 x 13 amp |
| Dimensions | W500mm x D520mm x H373mm |
| Product Approvals | CE, UKCA |
| Warranty | Appliance warranty 24 months plus additional 36 months boiling tank warranty |

Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipindustries.co.uk'