

HYDROTAP G5 CLASSIC PLUS ALL-IN-ONE BOILING CHILLED 100/75 PLUS HOT & COLD (MAINS)







BOILING

CHILLED

HOT & COLD

FILTERED

UNFILTERED

Order Code H56702Z00UK

Get instant filtered boiling and chilled water plus hot and cold water for your office or workplace from the Zip Water HydroTap All-in-One Classic Plus in bright chrome.

H56702Z00UK
Commercial
20
100
75
75



Tap HydroTap Classic Plus All-in-One bright chrome Water Pressure Min 1.7 bar - Max 5 bar Water Connection 1/2" BSP Water Supply Cold & Hot Requirements Water Valves Integrated dual check valve Power Rating 1.9kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W280mm x D478mm x H333mm Product Approvals CE, UKCA Warranty Appliance warranty 24 months plus additional 36 months boiling tank warranty		
Water Connection 1/2" BSP Water Supply Cold & Hot Requirements Water Valves Integrated dual check valve Power Rating 1.9kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W280mm x D478mm x H333mm Product Approvals CE, UKCA	Тар	HydroTap Classic Plus All-in-One bright chrome
Water Supply Requirements Water Valves Integrated dual check valve Power Rating 1.9kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W280mm x D478mm x H333mm Product Approvals CE, UKCA	Water Pressure	Min 1.7 bar - Max 5 bar
Requirements Water Valves Integrated dual check valve Power Rating 1.9kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W280mm x D478mm x H333mm Product Approvals CE, UKCA	Water Connection	1/2" BSP
Power Rating 1.9kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W280mm x D478mm x H333mm Product Approvals CE, UKCA	• • •	Cold & Hot
Power Supply 1 x 13 amp Dimensions W280mm x D478mm x H333mm Product Approvals CE, UKCA	Water Valves	Integrated dual check valve
Dimensions W280mm x D478mm x H333mm Product Approvals CE, UKCA	Power Rating	1.9kW 230v 50/60 Hz
Product Approvals CE, UKCA	Power Supply	1 x 13 amp
	Dimensions	W280mm x D478mm x H333mm
Warranty Appliance warranty 24 months plus additional 36 months boiling tank warranty	Product Approvals	CE, UKCA
	Warranty	Appliance warranty 24 months plus additional 36 months boiling tank warranty

Installation Requirements

^{&#}x27;1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipindustries.co.uk'