

HYDROTAP G5 CLASSIC PLUS ALL-IN-ONE BOILING CHILLED SPARKLING 140/75 PLUS HOT & COLD (VENTED)









BOILING

CHILLED

SPARKLING

HOT & COLD

FILTERED

UNFILTERED

Order Code H5B777Z00UK

Get instant filtered boiling, chilled and sparkling water plus hot and cold water for your office or workplace from the Zip Water HydroTap All-in-One Classic Plus.

| Manufacturing Code | H5B777Z00UK |
|---|-------------|
| Capacity | Commercial |
| Number of people | 40 |
| Boiling Cups per hour | 140 |
| Chilled Cups per hour | 175 |
| Chilled Litres per hour | 175 |
| Combined Chilled and Sparkling Cups per hour | 175 |
| Combined Chilled and Sparkling Litres per hour | 175 |
| | |



| Тар | HydroTap Classic Plus All-in-One bright chrome |
|------------------------------|--|
| Water Pressure | Min 2.5 bar - Max 5 bar |
| Water Connection | 1/2" BSP |
| Water Supply Requirements | Cold & Hot |
| Water Valves | Integrated dual check valve |
| Power Rating | 1.96kW 230v 50/60 Hz |
| Booster Power Rating | 2.2kW at 230V |
| Power Supply | 2 x 13 amp |
| Dimensions | W280mm x D483mm x H333mm |
| Product Approvals | CE, UKCA |
| Warranty | Appliance warranty 24 months plus additional 36 months boiling tank warranty |
| | |

Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipindustries.co.uk'