



# HYDROTAP G5 ARC PLUS BOILING CHILLED 240/175



**BOILING**



**CHILLED**

**FILTERED**

Order Code H5L705Z09UK

Get instant filtered boiling and chilled water for your office or workplace from the Zip Water HydroTap Arc Plus in bright chrome.

---

Manufacturing Code H5L705Z09UK

---

Capacity Commercial

---

Number of people 100

---

Boiling Cups per hour 240

---

Chilled Cups per hour 175

---

Chilled Litres per hour 175

---



|                                  |  |
|----------------------------------|--|
| <b>Tap</b>                       | HydroTap Arc Plus gunmetal   |
| <b>Water Pressure</b>            | Min 1.7 bar - Max 5 bar  |
| <b>Water Connection</b>          | 1/2" BSP   |
| <b>Water Supply Requirements</b> | Cold   |
| <b>Water Valves</b>              | Integrated dual check valve  |
| <b>Power Rating</b>              | 2.1kW 230v 50/60 Hz  |
| <b>Booster Power Rating</b>      | 2.2kW at 230V  |
| <b>Power Supply</b>              | 2 x 13 amp   |
| <b>Dimensions</b>                | W500mm x D520mm x H373mm   |
| <b>Product Approvals</b>         | CE, UKCA   |
| <b>Warranty</b>                  | Appliance warranty 24 months plus additional 36 months boiling tank warranty |

## Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipindustries.co.uk](http://www.zipindustries.co.uk)'