

HYDROTAP G5 TOUCH FREE WAVE CHILLED 175



FILTERED

Order Code H5W711Z00UK

Get instant filtered contactless chilled tap water for your office or workplace from the Zip Water Touch Free Wave.

Manufacturing Code	H5W711Z00UK
Capacity	Commercial
Number of people	61-100
Chilled Cups per hour	175
Chilled Litres per hour	175
Combined Chilled and Sparkling Cups per hour	175
Combined Chilled and Sparkling Litres per hour	175



Tap HydroTap Touch Free Wave bright chrome Water Pressure Min 1.7 bar - Max 5 bar Water Connection 1/2" BSP Water Supply Requirements Water Valves Integrated dual check valve Power Rating 0.34kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA Warranty Appliance warranty 24 months plus additional 36 months boiling tank warranty		
Water Connection1/2" BSPWater Supply RequirementsColdWater ValvesIntegrated dual check valvePower Rating0.34kW 230v 50/60 HzPower Supply1 x 13 ampDimensionsW500mm x D520mm x H373mmProduct ApprovalsCE, UKCA	Тар	HydroTap Touch Free Wave bright chrome
Water Supply Requirements Water Valves Integrated dual check valve Power Rating 0.34kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Water Pressure	Min 1.7 bar - Max 5 bar
Requirements Water Valves Integrated dual check valve Power Rating 0.34kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Water Connection	1/2" BSP
Power Rating 0.34kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA		Cold
Power Supply 1 x 13 amp Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Water Valves	Integrated dual check valve
Dimensions W500mm x D520mm x H373mm Product Approvals CE, UKCA	Power Rating	0.34kW 230v 50/60 Hz
Product Approvals CE, UKCA	Power Supply	1 x 13 amp
	Dimensions	W500mm x D520mm x H373mm
Warranty Appliance warranty 24 months plus additional 36 months boiling tank warranty	Product Approvals	CE, UKCA
	Warranty	Appliance warranty 24 months plus additional 36 months boiling tank warranty

Installation Requirements

^{&#}x27;1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipindustries.co.uk'