

HYDROTAP G5 TOUCH FREE WAVE BOILING CHILLED SPARKLING 100/75







BOILING

CHILLED

SPARKLING

FILTERED

Order Code H5W760Z03UK

The Zip Water HydroTap Touch Free Wave in bright chrome provides instant filtered boiling, chilled and sparkling tap water for your office or workplace.

Manufacturing Code	H5W760Z03UK
Capacity	Commercial
Number of people	1-20
Boiling Cups per hour	100
Chilled Cups per hour	75
Chilled Litres per hour	75
Combined Chilled and Sparkling Cups per hour	75
Combined Chilled and Sparkling Litres per hour	75



Tap HydroTap Touch Free Wave matt black Water Pressure Min 2.5 bar - Max 5 bar Water Connection 1/2" BSP Water Supply Requirements Water Valves Integrated dual check valve Power Rating 1.96kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W339mm x D483mm x H333mm Product Approvals CE, UKCA Warranty Appliance warranty 24 months plus additional 36 months boiling tank warranty		
Water Connection1/2" BSPWater Supply RequirementsColdWater ValvesIntegrated dual check valvePower Rating1.96kW 230v 50/60 HzPower Supply1 x 13 ampDimensionsW339mm x D483mm x H333mmProduct ApprovalsCE, UKCA	Тар	HydroTap Touch Free Wave matt black
Water Supply Requirements Water Valves Integrated dual check valve Power Rating 1.96kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W339mm x D483mm x H333mm Product Approvals CE, UKCA	Water Pressure	Min 2.5 bar - Max 5 bar
Requirements Water Valves Integrated dual check valve Power Rating 1.96kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W339mm x D483mm x H333mm Product Approvals CE, UKCA	Water Connection	1/2" BSP
Power Rating 1.96kW 230v 50/60 Hz Power Supply 1 x 13 amp Dimensions W339mm x D483mm x H333mm Product Approvals CE, UKCA		Cold
Power Supply 1 x 13 amp Dimensions W339mm x D483mm x H333mm Product Approvals CE, UKCA	Water Valves	Integrated dual check valve
Dimensions W339mm x D483mm x H333mm Product Approvals CE, UKCA	Power Rating	1.96kW 230v 50/60 Hz
Product Approvals CE, UKCA	Power Supply	1 x 13 amp
	Dimensions	W339mm x D483mm x H333mm
Warranty Appliance warranty 24 months plus additional 36 months boiling tank warranty	Product Approvals	CE, UKCA
	Warranty	Appliance warranty 24 months plus additional 36 months boiling tank warranty

Installation Requirements

1. Installation and connection of your Zip HydroChill must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections within 1 metre of the product.3. Discrete cabinetry cut-outs are required for ventilation.4. Installation for HydroChill 50 on most bench tops is straightforward, however some stone bench tops may require a specialised cutting service.5. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.co.uk